CFMEU SAFETY ALERT

RECOMMENDED WIND SPEEDS FOR SAFE USE OF PLANT

Authored by Bob Benkesser on 23rd January 2019

PLANT	METRES PER	KILOMETRES	KNOTS
	SECOND	PER HOUR	
NARROW EWP SCISSOR	5	18	9.72
MAN BOX	7	25.2	13.61
MOBILE CRANE	10	36	19.44
WIDE EWP OR KNUCKLE	12.5	45	24.3
BOOM			
TRUCK MOUNTED CONCRETE	15	54	29.16
PUMP			
TOWER CONCRETE PUMP	20	72	38.88
TOWER CRANE	20	72	38.88
MATERIAL & PERSONNEL	20	72	38.88
HOIST			
ERECTION / DISMANTLING	12.5	45	24.3
OF MATERIAL & PERSONNEL			
HOIST			

- The above wind speeds are the maximum recommended wind speeds taken from the manufacturers operating manual and the relevant Australian Standards for operating that particular item of plant;
- If your company has a lower wind speed in their procedures then that is the higher standard and must be complied with;
- If the operator believes it is unsafe to operate plant at conditions below these recommended wind speeds, the operator has the ultimate responsibility to make the final decision.

If you are being pressured into operating plant in conditions you consider unsafe contact the CFMEU office.

REPORT UNSAFE WORK PRACTICES CALL (08) 9228 6900 OR EMAIL SAFETY@CFMEUWA.COM

Safety is union business. CFMEU Stand up. Speak out. Come home.

AUTHORISED MICK BUCHAN, STATE SECRETART CFMEU WA, 80 BEAUFORT STREET PERTH